



TECHNICAL DATA SHEET



TYPE	DucoSun Cubic 200x37 - Assembly plate
DESCRIPTION	External permanent solar shading system with fixed blades
SHAPE OF BLADE	Rectangular louvre blade
DIMENSIONS	200 mm x 37 mm
MATERIAL	Aluminium : EN AW-6063 T66 (EN 573-3) Profile thickness : min. 1,5 mm
ANGLE (E) AND STEP (S)	To be determined according to project
MAX. SPAN	4000 mm @ 800Pa
ASSEMBLY PLATE	Aluminium plates - thickness 5 mm (AlMgSi0,5)
FIXATION BLADE	Self-tapping countersunk bolt M6x30 DIN7500-MZ (AISI 304)
FIXATION ASSEMBLY PLATE	On Duco mullion (Ø9) or directly against the underlying structure (Ø12).
REACTION TO FIRE	A2-s1,d0 (EN13501-1)
SURFACE TREATMENT	- Standard aluminium anodised (15-20µm) according Qualanod - Polyester powder coated (60-80µm) according Qualicoat Seaside type A
OPTIONS	- Contour assembly plate : rectangular / blade shaped




3

2


1

D



C

B




A

D

C

B

A

DucoSun **Cubic 200x37** Assembly plate - 0°

Date : 10/09/2024

Scale: 1/7,5

DUCO
Ventilation & Sun ControlBedrijvenlaan 2 - 8630 VEURNE
tel. 0032-58/330066 - fax.0032-58/330067
email: info@duco.eu www.duco.euThis drawing is the property of Duco Projects NV and cannot be copied or shown
to a third party without prior written authorisation from Duco Projects NV.

Tol. : ISO 2768-mK

Mat. :

Format : A3

outline:

mm

weight:

kg/m

coat. surf:

dm²/m

Draftsman: JHX

Ref nr. :

Drawing nr. :

TF_Cubic 200x37_AP

3

2

1